

Tent image



Technical data

<b>Clear-span width</b>	600 cm
<b>Side height</b>	229 cm
<b>Ridge height</b>	338 cm
<b>Highest point</b>	488 cm
<b>Roof pitch</b>	20°
<b>Bay distance</b>	300 cm
<b>Gable uprights</b>	1 gable upright (per end)
<b>Longest component</b>	350 cm
<b>Minimum tent length</b>	1200 cm
<b>Maximum tent length</b>	No limit
<b>Main profile</b>	81 mm x 48 mm x 3 mm (optional 94 mm x 48 mm x 3 mm )
<b>Eave / corner connection</b>	Internal eave insert
<b>Max. allowed wind speed to DIN</b>	80 km/h
<b>Wind Load</b>	0.3 kN/m <sup>2</sup>
<b>Extension / lean-to options</b>	1/2 hexagonal at gable end With all Mega tents Extension
<b>Flooring options</b>	Woodenfloor with timber or steel sub-construction Aluminium cassettefloor with plywood or full aluminiumboards Compactfloor
<b>Cover</b>	RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2
<b>Note</b>	All Mega variations fit 6m and 8m standard party tents By using compactfloor anchoring can be omitted

Tent top and side view image

