

Tent image



Technical data

|                                       |                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------|
| <b>Clear-span width</b>               | 1750 cm                                                                       |
| <b>Side height</b>                    | 350 cm, 440cm                                                                 |
| <b>Ridge height</b>                   | 585 cm, 686cm                                                                 |
| <b>Roof pitch</b>                     | 15°                                                                           |
| <b>Bay distance</b>                   | 250 cm                                                                        |
| <b>Gable uprights</b>                 | 4 gable uprights (per end)                                                    |
| <b>Longest component</b>              | 915 cm, 917cm                                                                 |
| <b>Minimum tent length</b>            | 1500 cm                                                                       |
| <b>Maximum tent length</b>            | No limit                                                                      |
| <b>Main profile</b>                   | 170 mm x 88 mm x 3 mm                                                         |
| <b>Door sizes (PVC door panels)</b>   | Side wall 220 cm x 300 cm Gable end 450 cm x 390 cm                           |
| <b>Eave / corner connection</b>       | Internal eave insert                                                          |
| <b>Max. allowed wind speed to DIN</b> | 100 km/h                                                                      |
| <b>Wind Load</b>                      | 0.5 kN/m <sup>2</sup>                                                         |
| <b>Snow load</b>                      | 0.25 kN/m <sup>2</sup> , 0.75 kN/m <sup>2</sup>                               |
| <b>Cover</b>                          | RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2 |
| <b>Special design</b>                 | Sliding doors, rolling doors or service entrances<br>Trapezoidal metal sheets |

Tent top and side view image

