

Tent image



Technical data

<b>Clear-span width</b>	1000 cm
<b>Side height</b>	240 cm, 300 cm
<b>Ridge height</b>	422 cm, 482 cm
<b>Roof pitch</b>	20°
<b>Bay distance</b>	500 cm
<b>Gable uprights</b>	1 gable upright (per end)
<b>Longest component</b>	538 cm
<b>Minimum tent length</b>	1000 cm
<b>Maximum tent length</b>	No limit
<b>Main profile</b>	130 mm x 70 mm x 3 mm
<b>Eave / corner connection</b>	Internal eave insert
<b>Max. allowed wind speed to DIN</b>	100 km/h
<b>Wind Load</b>	0.5 kN/m <sup>2</sup>
<b>Extension / lean-to options</b>	Extension (max. span 300 cm located anywhere, both sides, any length), 1/2 octagonal with intermediate bays,

**Flooring options**

**Cover**

**Special design**

one or both sides with Giga tents

Woodenfloor with timber or steel sub-construction

Aluminium cassettefloor with plywood or full

aluminiumboards Compactfloor

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Portal beams can be used in place of cross struts By using compactfloor anchoring can be omitted

Tent top and side view image

